



CHIP SPREADER (SERIES HD+)

TECHNICAL DATA:

Type	Availability	Line spreader	Disc spreader	Spreading width [m]	Storage capacity [l]
HLS 170	HD+ 70i, HD+ 80i, HD+ 90i, HD+ 110i	•		0.30-1.70	960
HDS 18	HD+ 70i, HD+ 80i, HD+ 90i, HD+ 110i		•	1.00-8 (depending on the material)	750

HLS 150 AND HLS 170: AN OVERVIEW (HLS = HAMM LINE SPREADER):

- ◇ One size, suitable for the drum widths of the HD+ 70i (1500 mm) and the HD+ 80i, HD+ 90i, HD+ 110i (1680 mm)
 - ◇ Excellent, even spreading pattern
 - ◇ Precise spreading width
 - ◇ Regulation of spreading quantity: Constant spreading quantity, even when travelling quickly or on an inline
 - ◇ Speed-dependent application of chips
 - ◇ Convenient, electronic spreading quantity adjustment
 - ◇ Great access to hydraulic systems and all maintenance points
 - ◇ Convenient attachment thanks to the quick coupling, quick filling
 - ◇ Holder with the aid of the forklift pockets or the lifting eyes
 - ◇ Bracket (rigid) with three-point mounting bracket and without drum protrusion
 - ◇ Rear-view camera (mandatory option)
-
- ① Convenient spreading width adjustment via five or six segments
 - ② Convenient quick emptying Selbstaufrollende Abdeckplane
 - ③ Self-retracting tarpaulin
 - ④ Spotlight with front-grille guard
 - ⑤ Rear-view camera for optimum visibility
 - ⑥ Forklift pockets for the holder
 - ⑦ Lifting eyes inside the container
 - ⑧ Spreading plate for a fine spreading pattern



HDS 18 - AN OVERVIEW:

- ◇ Large spreading width
- ◇ Bracket (rigid) with three-point mounting bracket and without drum protrusion
- ◇ Chip quantity application as per preselection
- ◇ Rear-view camera for optimum visibility (required option)
- ◇ Convenient attachment thanks to the quick coupling
- ◇ Convenient quick emptying
- ◇ Made in Germany

