

AB 200 Extending Screed



The **AB 200 Extending Screed** designed for the small VÖGELE pavers stands out through accurate operation and achieves high precompaction. It is available in 2 versions as far as equipment with compacting systems is concerned. AB 200 V (with vibrators) has been specially designed for use with SUPER 700, AB 200 TV (with tamper and vibrators) combines with SUPER 800.

The AB 200 Extending Screed, in either version, has a basic width of 1.1m and extends hydraulically to 2m. By addition of bolt-on extensions, the AB 200 V and TV builds up to a maximum width of 3.2m.

Specification AB 200

► Screed Versions V, TV ► Maximum Pave Width 3.2m

Pave Widths	0.5m to 3.2m
Basic Width	1.1m
Infinitely Variable Range	2m
Larger Widths	
Bolt-on Extensions	35cm to 2.7m (AB 200 V/TV)
	60cm to 3.2m (AB 200 V/TV)
Reduction in Width	
Infinitely Variable Range	0.5m to 1.1m
Crown Adjustment	
Mechanical	-2% to +4%

Compacting Systems	
Screed Versions	V, TV
Tamper (T)	tamper speed up to 1,800 rpm tamper stroke 4mm
Vibrators (V)	eccentric vibrators, frequency up to 50 Hz
Screed Heating	screed plates and tamper bars heated electrically by heating rods
Dimensions and Weights (Basic Screed)	
Width	1.1m (no end plates fitted)
Depth	0.7m
Weights	600kg (AB 200 V) 720kg (AB 200 TV)

Key: T = equipped with Tamper
V = equipped with Vibrators

Technical alterations reserved.