

Technical data

HX 70i VT-S



Tandem rollers Series HX

Tandem roller with vibrating roller drum and set of wheels

H297

HIGHLIGHTS

- > High compaction quality through optimum setting of the compaction parameters
- > Intelligent water sprinkler system
- > Operating concept Easy Drive
- > Innovative cabin concept for optimal visibility and high comfort
- > Digital ready

TECHNICAL DATA HX 70i VT-S (H297)

Weights

Operating weight with cab	kg	7750
Empty weight without cab, without ROPS	kg	6725
Maximum operating weight	kg	10340
Axle load, front/rear	kg	3990/3760
Axle load at maximum operating weight, front/rear	kg	3560/6780
Static linear load, front	kg/cm	26,60
French classification, value/class		20,8/VX1
Wheel load per tyre, rear	kg	940

Machine dimensions

Total length	mm	4177
Total height with cab	mm	2960
Height loading, min.	mm	2170
Centre distance	mm	3000
Total width with cab	mm	1680
Maximum working width	mm	2770
Ground clearance, centre	mm	280
Kerb clearance, left/right	mm	610/610
Turning radius, inside	mm	2800

Drum dimensions

Drum width, front	mm	1500
Drum diameter, front	mm	1140
Drum thickness, front	mm	17
Drum type, front		Smooth/split
Track offset, left/right	mm	1270

Tyre dimensions

Tyre size, rear		11.00-20
Width over tyres, rear	mm	1490
Number of tyres, rear		4

Diesel engine

Manufacturer		Kubota
Model		V3307-CR-TE5AB
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		54,6/74,3/2200
Power SAE J1349, kW/HP/rpm		55,4/74,2/2200
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF

Travel drive

Speed, infinitely variable	km/h	0-11,1
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	39/43

Vibration

Vibration frequency, front, I/II	Hz	42/50
Amplitude, front, I/II	mm	0,58/0,40
Centrifugal force, front, I/II	kN	63,23/62,57

Steering

Pendulum angle +/-	°	4
Steering, type		All-wheel, analogue

Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

Tank capacity/filling capacity

Fuel tank, capacity	L	148
Water tank, capacity	L	740

Sound level

Sound power level L(WA), guaranteed	db(A)	104
Sound power level L(WA), representative measurement	db(A)	103

EQUIPMENT

Scrapers foldable | Easy Drive operating concept | Pressure water sprinkling system | ECO mode | Frequency control | Speed preselect | Track offset, hydraulic | Automatic vibration system | Water filter system (3-fold) | Central water outlet | Camera system, front and rear | Working spotlights

OPTIONAL EQUIPMENT

ROPS cab with split doors | Heating and air-conditioning system | Tachograph | Bluetooth interface for Smart Doc | Smart Compact | Weather station | Edge pressing and cutting equipment | Chip spreader | Thermal aprons | HAMM Compaction Meter (HCM) | Speedometer | Automatic engine stop | HAMM Temperature Meter (HTM) | Back-up alarm | JDLink | Drum edge lighting | Drum lighting | Coming Home function