

Technical data

HD+ 140i VV-HF



Tandem rollers Series HD+
Tandem roller with two vibrating roller drums

H304

HIGHLIGHTS

- > Operating concept Easy Drive
- > 3-point articulation for even weight distribution and excellent on-centre feel
- > Innovative cabin concept for optimal visibility and high comfort
- > Seat operating unit can be moved and rotated
- > Digital ready

TECHNICAL DATA HD+ 140i VV-HF (H304)

Weights

Operating weight with cab	kg	13740
Operating weight with ROPS	kg	13510
Empty weight without cab, without ROPS	kg	12425
Max. operating weight	kg	14770
Axle load, front/rear	kg	6880/6860
Static linear load, front/rear	kg/cm	32,15/32,06
French classification, value/class		25,03/VT1

Machine dimensions

Total length	mm	5300
Total height with cab	mm	2980
Total height with ROPS	mm	3030
Height loading, min.	mm	2140
Centre distance	mm	3900
Total width with cab	mm	2260
Maximum working width	mm	2310
Ground clearance, centre	mm	340
Kerb clearance, left/right	mm	900/900
Turning radius, inside	mm	6200

Drum dimensions

Drum width, front/rear	mm	2140/2140
Drum diameter, front/rear	mm	1400/1400
Drum thickness, front/rear	mm	19/19
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm	170

Diesel engine

Manufacturer		DEUTZ
Model		TCD 4.1 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		115,0/156,4/2300
Power SAE J1349, kW/HP/rpm		115,0/154,1/2300
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

Travel drive

Speed, infinitely variable	km/h	0-10,5
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	35/39

Vibration

Vibration frequency, front, I/II	Hz	45/67
Vibration frequency, rear, I/II	Hz	45/67
Amplitude, front, I/II	mm	0,65/0,20
Amplitude, rear, I/II	mm	0,65/0,20
Centrifugal force, front, I/II	kN	160/105
Centrifugal force, rear, I/II	kN	160/105

Steering

Swing angle +/-	°	10
Steering, type		Articulated steering

Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

Tank capacity/filling capacity

Fuel tank, capacity	L	260
AdBlue/SCR reducing agent tank, capacity	L	20
Water tank, capacity	L	1145

Sound level

Sound power level L(WA), representative measurement	db(A)	109
-----------------------------------------------------	-------	-----

EQUIPMENT

Folding scraper | Pressure water sprinkling system | ECO mode | Speed preselect | Track offset, hydraulic | Water filter system (3-fold) | Central water outlet

OPTIONAL EQUIPMENT

Heating and air-conditioning system | Tachograph | Bluetooth interface for Smart Doc | Smart Compact | Weather station | Edge pressing and cutting equipment | HAMM Compaction Meter (HCM) | HAMM Temperature Meter (HTM) | Camera system | JDLink | Working spotlights | Drum edge lighting | Coming Home function